LA-UR-14-20287

Approved for public release; distribution is unlimited.

Title: Measuring x-ray spectra with a Compton electron spectrometer

Author(s): Espy, Michelle A.

Gehring, Amanda E.

Intended for: For program development

Issued: 2014-01-16



Disclaimer:

Disclaimer:
Los Alamos National Laboratory, an affirmative action/equal opportunity employer,is operated by the Los Alamos National
Security, LLC for the National NuclearSecurity Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396.
By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.
Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Departmentof Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Measuring x-ray spectra with a Compton electron spectrometer

Michelle Espy, Mandie Gehring






UNCLASSIFIED


X-rays Compton scatter into easier-to-detect electrons


Most electrons are forward

 Restricting angular acceptance of Compton electrons, incoming gamma energies & ejected electron momenta are simply related

Magnet relates energy to position












Demonstrated in various incarnations at NTS

- Morgan et al., NIM in Physics Research A308 (1991) 544-556
- Sale & Kammeraad SPIE Vol. 1734 Gamma-Ray Detectors (1992) p 279

Interesting features

- Distance electron crosses focal plane proportional to square root of electron momentum.
- Design achieves broad range of energies (from ~ 1 MeV/c up to 30 MeV/c)
- Reported electron momentum resolution is the larger of 0.1 MeV/c or 1% of momentum






Table 1 Summary of parameters for the two models

Compton
 electrons


	Sm-Co	Nd-Fe
Size [cm]	32×48×50	24×38×40
Weight [kg]	600	300
Energy range		
[MeV]	0.5 to 27	0.5 to 23
Focal plane		
[cm]	4 to 29	3 to 20
Field gradient		
[kG/cm]	0.35	0.65
Maximum field		
[kG]	10	12.5
Momentum		
resolution	<1% or 100 keV/c	<1% or 100 keV/c
Time resolution		
[ps]	200	200

Converter

foil

UNCLASSIFIED

Present spectrometer appears useful for a variety of places



Data at microtron taken with significant help from James Hunter and John Stearns, AET-06


Recent measurements at the "microtron"


- Bremsstrahlung X-ray source with endpoint energies 6, 10, 15, 20 MeV
- Tungsten collimation to ~ 5 mm
- Sweeper magnet
- Phosphor detection


Drop vacuum every energy change

- Unable to use graphite
 - ~ 5° angular acceptance

Excellent agreement w/ predicted energy endpoints








Data is on left - Model of expected electrons/cm vs position is on right



Turn back into gamma spectra



Solid = measured data reconverted to gamma position;

Dashed = Bremsstrahlung model; no correction for background, assumes energy independent response of phosphor



Summary of Results so far

- Electron endpoint energy in excellent agreement with our model
- Reconstructed spectra looks Bremsstrahlung-like (as we might expect)
- We plan to return next week to improve alignment and refine measurements

Work in progress

- Plans to calibrate with known energies
- Develop better collimation and shielding system
- Design of a better detector system





Energy Calibration

- ⁶⁰Co source at NSTec Source Range resolve 1.17 and 1.33 MeV lines?
- Will need to shield spectrometer for the first time
- 20 MeV High Repetition-Rate LINAC at Idaho Accelerator Center
- Will potentially measure 0.5-20 MeV electrons, 0.5 MeV step
- Focus on alignment issues





Fig. 13. Measured positions along the focal plane in the two spectrometers versus the square root of momentum. The error bars on the data are smaller than the symbol size. The solid curve is a fit to the data.



Detector System

- Evaluating 3 internal options: scintillator + optical fibers, scintillating fibers, or measurement of Cerenkov radiation from normal fibers
- Goals: Bin size ≤ 250 keV and ~ 1 ns time resolution
- Light detection from fibers: streak camera? PMT? Something else?








Path forward

- Measure DAHRT spectrum early next year (?, H. Hermann P-24)
- Build, test, and calibrate time-resolved detector system
- Determine and test detector system shielding
- Measure spectra at RITS
- In parallel, design and fabricate lower field magnet for Cygnus
 - Field currently 632 G/cm and electron energy range 1-20 MeV; 100 G/cm would shrink the range to 0.?-3 MeV
- Modify detector system if necessary for low-energy spectrometer
- Measure Cygnus spectrum
- Possible spectrum

measurements at other facilities



UNCLASSIFIED